

Strand Bamboo Click Engineered Construction Chart

Strand Bamboo Click Engineered	Type	Lgth	Width	Thick	Attached Pad	Surface Style	Wear Layer	SF/Box	Install	Radiant Heat
Chadwick Handscraped Click Engineered	Bamboo	6 ft	7-1/2	9/16		Flat/Smooth	3 mm	30.27	Float or Glue Down	Yes
Champagne Click Engineered	Bamboo	6 ft	5-5/8	9/16		Flat/Smooth	4 mm	22.62	Float or Glue Down	Yes
Mojave Click Engineered	Bamboo	6 ft	7-1/2	9/16		Antiqued	3 mm	30.27	Float or Glue Down	Yes
Sedona Click Engineered	Bamboo	6 ft	7-1/2	9/16		Flat/Smooth	3 mm	30.27	Float or Glue Down	Yes
Stockholm Click Engineered	Bamboo	4 ft / 2 ft	7-1/2	9/16		Cross Brushed	3 mm	22.43	Float or Glue Down	Yes
Tawny Click Engineered	Bamboo	6 ft	5-5/8	9/16		Flat/Smooth	4 mm	22.62	Float or Glue Down	Yes
Tierra Handscraped Click Engineered	Bamboo	6 ft	7-1/2	9/16		Flat/Smooth	3 mm	30.27	Float or Glue Down	Yes
Timber Antiqued Click Engineered	Bamboo	6 ft	7-1/2	9/16		Flat/Smooth	3 mm	30.27	Float or Glue Down	Yes
Trondheim Click Engineered	Bamboo	4 ft / 2 ft	7-1/5	9/16		Textured	3 mm	22.45	Float or Glue Down	Yes
Tundra Antiqued Click Engineered	Bamboo	6 ft	5-5/8	9/16		Antiqued	4 mm	22.62	Float or Glue Down	Yes