

PRODUCT SPECIFICATIONS

Natures View Style Rustique 18" x 18" Luxury Vinyl Tile

| PRODUCT COMPOSITION | STANDARD/NORMS | DATA |
|--------------------------------|-----------------------|--|
| Manufacturing Standard | ASTM F1700-13 | Class III Printed Film Vinyl Tile, Type B Embossed Surface |
| Construction | ISO 2424 | Luxury Vinyl Tile |
| PRODUCT DIMENSIONS | | |
| Size (Tile) | | 18" x 18" |
| Overall Thickness | ASTM 2055 | 0.125" (3.175mm) |
| Wear Layer Thickness | EN429 | 40 mil (1.0mm) |
| Size & Squareness | ASTM 2055 | Passes |
| Weight per Tile | 18" x 18" | 2.08 lbs |
| Weight per Carton | 16 Tiles (36 sq. ft.) | 36lbs |
| PROPERTIES | | |
| Stability | ASTM 1514 | Passes |
| Abrasion Resistance | ASTM D3389 | 0.2849/5000 cycles |
| Static Load Limit | ASTM F970 (modified) | 2000 PSI |
| Sound Insulation | DIN 52210 | 4 dB |
| Static Coefficient of Friction | ASTM D2047 | 0.61 (Exceeds ADA Standards) |
| Chemical Resistance | ASTM 925 | Passes (Excellent) |
| Light Resistance | F 1515 | Passes |
| Indentation Resistance | F 1914 | Passes (< 8%) |
| FLAMMABILITY RATINGS | | |
| Radiant Panel Test | ASTM E648 | Class 1 |
| Smoke Density | ASTM E662 | Passes (<450 sdi) |
| Heat Stability | ASTM 1514 | Passes |
| HUD/FHA Requirements | | Exceeds |

